



## ESP32-P4-Function-EV-Board

[\[中文\]](#)

This user guide will help you get started with ESP32-P4-Function-EV-Board and will also provide more in-depth information.

ESP32-P4-Function-EV-Board is a multimedia development board based on the ESP32-P4 chip. ESP32-P4 chip features a dual-core 400 MHz RISC-V processor and supports up to 32 MB PSRAM. In addition, ESP32-P4 supports USB 2.0 specification, MIPI-CSI/DSI, H264 Encoder, and various other peripherals. With all of its outstanding features, the board is an ideal choice for developing low-cost, high-performance, low-power network-connected audio and video products.

The 2.4 GHz Wi-Fi 6 & Bluetooth 5 (LE) module ESP32-C6-MINI-1 serves as the Wi-Fi and Bluetooth module of the board. The board also includes a 7-inch capacitive touch screen with a resolution of 1024 x 600 and a 2MP camera with MIPI CSI, enriching the user interaction experience. The development board is suitable for prototyping a wide range of products, including visual doorbells, network cameras, smart home central control screens, LCD electronic price tags, two-wheel vehicle dashboards, etc.

Most of the I/O pins are broken out to the pin headers for easy interfacing. Developers can connect peripherals with jumper wires.



*ESP32-P4-Function-EV-Board*



The document consists of the following major sections:

- [Getting Started](#): Overview of ESP32-P4-Function-EV-Board and hardware/software setup instructions to get started.
- [Hardware Reference](#): More detailed information about the ESP32-P4-Function-EV-Board's hardware.
- [Hardware Revision Details](#): Revision history, known issues, and links to user guides for previous versions (if any) of ESP32-P4-Function-EV-Board.
- [Related Documents](#): Links to related documentation.

## Getting Started

This section provides a brief introduction to ESP32-P4-Function-EV-Board, instructions on how to do the initial hardware setup and how to flash firmware onto it.

## Description of Components



The key components of the board are described in a clockwise direction.

Key Component	Description
J1	All available GPIO pins are broken out to the header block J1 for easy interfacing. For more details, see <a href="#">Header Block</a> .
ESP32-C6 Module Programming Connector	The connector can be used with ESP-Prog or other UART tools to flash firmware onto the ESP32-C6 module.


Key Component	Description
ESP32-C6-MINI-1 Module	This module serves as the Wi-Fi and Bluetooth communication module for the board.
Microphone	Onboard microphone connected to the interface of Audio Codec Chip.
Reset Button	Resets the board.
Audio Codec Chip	ES8311 is a low-power mono audio codec chip. It includes a single-channel ADC, a single-channel DAC, a low-noise pre-amplifier, a headphone driver, digital sound effects, analog mixing, and gain functions. It interfaces with the ESP32-P4 chip over I2S and I2C buses to provide hardware audio processing independent of the audio application.
Speaker Output Port	This port is used to connect a speaker. The maximum output power can drive a 4 $\Omega$ , 3 W speaker. The pin spacing is 2.00 mm (0.08").
Audio PA Chip	NS4150B is an EMI-compliant, 3 W mono Class D audio power amplifier that amplifies audio signals from the audio codec chip to drive speakers.
5 V to 3.3 V LDO	A power regulator that converts a 5 V supply to a 3.3 V output.
BOOT Button	The boot mode control button. Press the <b>Reset Button</b> while holding down the <b>Boot Button</b> to reset ESP32-P4 and enter firmware download mode. Firmware can then be downloaded to SPI flash via the USB-to-UART Port.
Ethernet PHY IC	Ethernet PHY chip connected to the ESP32-P4 EMAC RMII interface and RJ45 Ethernet Port.
Buck Converter	A buck DC-DC converter for the 3.3 V power supply.
USB-to-UART Bridge Chip	CP2102N is a single USB-to-UART bridge chip connected to the ESP32-P4 UART0 interface, CHIP_PU, and GPIO35 (strapping pin). It provides transfer rates up to 3 Mbps for firmware downloading and debugging, supporting the automatic download functionality.
5 V Power-on LED	This LED lights up when the board is powered through any USB Type-C port.
RJ45 Ethernet Port	An Ethernet Port supporting 10/100 Mbps adaptive.
USB-to-UART Port	The USB Type-C port can be used to power the board, flash firmware to the chip, and communicate with the ESP32-P4 chip via the USB-to-UART Bridge Chip.
USB Power-in Port	The USB Type-C port used to power the board.
USB 2.0 Type-C Port	The USB 2.0 Type-C Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB device connecting to a USB host. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously. USB 2.0 Type-C Port can also be used for powering the board.
USB 2.0 Type-A Port	The USB 2.0 Type-A Port is connected to the USB 2.0 OTG High-Speed interface of ESP32-P4, compliant with the USB 2.0 specification. When communicating with other devices via this port, ESP32-P4 acts as a USB host, providing up to 500 mA of current. Please note that USB 2.0 Type-C Port and USB 2.0 Type-A Port cannot be used simultaneously.
Power Switch	Power On/Off Switch. Toggling toward the ON sign powers the board on (5 V), toggling away from the ON sign powers the board off.
Switch	TPS2051C is a USB power switch that provides a 500 mA output current limit.
MIPI CSI Connector	The FPC connector 1.0K-GT-15PB is used for connecting external camera modules to enable image transmission. For details, please refer to 1.0K-GT-15PB specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.

Key Component	Description
Buck Converter	A buck DC-DC converter for VDD_HP power supply of ESP32-P4.
ESP32-P4	A high-performance MCU with large internal memory and powerful image and voice processing capabilities.
40 MHz XTAL	An external precision 40 MHz crystal oscillator that serves as a clock for the system.
32.768 kHz XTAL	An external precision 32.768 kHz crystal oscillator that serves as a low-power clock while the chip is in deep-sleep mode.
MIPI DSI Connector	The FPC connector 1.0K-GT-15PB is used for connecting displays. For details, please refer to 1.0K-GT-15PB Specification in Related Documents. FPC specifications: 1.0 mm pitch, 0.7 mm pin width, 0.3 mm thickness, 15 pins.
SPI flash	The 16 MB flash is connected to the chip via the SPI interface.
MicroSD Card Slot	The development board supports a MicroSD card in 4-bit mode and can store or play audio files from the MicroSD card.

## Accessories

Optionally, the following accessories are included in the package:

- LCD and its accessories (optional)
  - 7-inch capacitive touch screen with a resolution of 1024 x 600
  - LCD adapter board
  - Accessories bag, including DuPont wires, ribbon cable for LCD, long standoffs (20 mm in length), and short standoffs (8 mm in length)
- Camera and its accessories (optional)
  - 2MP camera with MIPI CSI
  - Camera adapter board
  - Ribbon cable for camera



*Ribbon Cables in Forward and Reverse Directions*

### Note

Please note that the ribbon cable in the **forward direction**, whose strips at the two ends are on the same side, should be used for the **camera**; the ribbon cable in the **reverse direction**, whose strips at the two ends are on different sides, should be used for the **LCD**.



## Start Application Development

Before powering up your ESP32-P4-Function-EV-Board, please make sure that it is in good condition with no obvious signs of damage.

### Required Hardware

- ESP32-P4-Function-EV-Board
- USB cables
- Computer running Windows, Linux, or macOS

#### Note

Be sure to use a good quality USB cable. Some cables are for charging only and do not provide the needed data lines nor work for programming the boards.

### Optional Hardware

- MicroSD card

### Hardware Setup

Connect the ESP32-P4-Function-EV-Board to your computer using a USB cable. The board can be powered through any of the USB Type-C ports. The USB-to-UART Port is recommended for flashing firmware and debugging.

To connect the LCD, follow these steps:

1. Secure the development board to the LCD adapter board by attaching the short copper standoffs (8 mm in length) to the four standoff posts at the center of the LCD adapter board.
2. Connect the J3 header of the LCD adapter board to the MIPI DSI connector on the ESP32-P4-Function-EV-Board using the LCD ribbon cable (**reverse direction**). Note that the LCD adapter board is already connected to the LCD.
3. Use a DuPont wire to connect the RST\_LCD pin of the J6 header of the LCD adapter board to the GPIO27 pin of the J1 header on the ESP32-P4-Function-EV-Board. The RST\_LCD pin can be configured via software, with GPIO27 set as the default.
4. Use a DuPont wire to connect the PWM pin of the J6 header of the LCD adapter board to the GPIO26 pin of the J1 header on the ESP32-P4-Function-EV-Board. The PWM pin can be configured via software, with GPIO26 set as the default.
5. It is recommended to power the LCD by connecting a USB cable to the J1 header of the LCD adapter board. If this is not feasible, connect the 5V and GND pins of the LCD adapter board to corresponding pins on the J1 header of the ESP32-P4-Function-EV-Board, provided that the development board has sufficient power supply.
6. Attach the long copper standoffs (20 mm in length) to the four standoff posts on the periphery of the LCD adapter board to allow the LCD to stand upright.

In summary, the LCD adapter board and ESP32-P4-Function-EV-Board are connected via the following pins:

LCD Adapter Board	ESP32-P4-Function-EV
J3 header	MIPI DSI connector
RST_LCD pin of J6 header	GPIO27 pin of J1 header
PWM pin of J6 header	GPIO26 pin of J1 header
5V pin of J6 header	5V pin of J1 header
GND pin of J6 header	GND pin of J1 header

#### Note

- If you power the LCD adapter board by connecting a USB cable to its J1 header, you do not need to connect its 5V and GND pins to the corresponding pins on the development board.
- To use the camera, connect the camera adapter board to the MIPI CSI connector on the development board using the camera ribbon cable (**forward direction**).

## Software Setup


To set up your development environment and flash an application example onto your board, please follow the instructions in [ESP-IDF Get Started](#).

You can find examples for ESP32-P4-Function-EV by accessing [Examples](#). To configure project options, enter `idf.py menuconfig` in the example directory.

## Hardware Reference

### Block Diagram

The block diagram below shows the components of ESP32-P4-Function-EV-Board and their interconnections.



ESP32-P4-Function-EV-Board (click to enlarge)

## Power Supply Options

Power can be supplied through any of the following ports:

- USB 2.0 Type-C Port
- USB Power-in Port
- USB-to-UART Port

If the USB cable used for debugging cannot provide enough current, you can connect the board to a power adapter via any available USB Type-C port.

## Header Block

The tables below provide the **Name** and **Function** of the pin header J1 of the board. The pin header names are shown in Figure [ESP32-P4-Function-EV-Board - front \(click to enlarge\)](#). The numbering is the same as in the [ESP32-P4-Function-EV-Board Schematic](#).

### J1

No.	Name	Type <sup>1</sup>	Function
1	3V3	P	3.3 V power supply
2	5V	P	5 V power supply
3	7	I/O/T	GPIO7
4	5V	P	5 V power supply
5	8	I/O/T	GPIO8



No.	Name	Type	Function
6	GND	GND	Ground
7	23	I/O/T	GPIO23
8	37	I/O/T	U0TXD, GPIO37
9	GND	GND	Ground
10	38	I/O/T	U0RXD, GPIO38
11	21	I/O/T	GPIO21
12	22	I/O/T	GPIO22
13	20	I/O/T	GPIO20
14	GND	GND	Ground
15	6	I/O/T	GPIO6
16	5	I/O/T	GPIO5
17	3V3	P	3.3 V power supply
18	4	I/O/T	GPIO4
19	3	I/O/T	GPIO3
20	GND	GND	Ground
21	2	I/O/T	GPIO2
22	NC(1)	I/O/T	GPIO1 <sup>2</sup>
23	NC(0)	I/O/T	GPIO0 <sup>2</sup>
24	36	I/O/T	GPIO36
25	GND	GND	Ground
26	32	I/O/T	GPIO32
27	24	I/O/T	GPIO24
28	25	I/O/T	GPIO25
29	33	I/O/T	GPIO33
30	GND	GND	Ground
31	26	I/O/T	GPIO26
32	54	I/O/T	GPIO54
33	48	I/O/T	GPIO48
34	GND	GND	Ground
35	53	I/O/T	GPIO53
36	46	I/O/T	GPIO46
37	47	I/O/T	GPIO47
38	27	I/O/T	GPIO27
39	GND	GND	Ground

No.	Name	Type	Function
40	NC(45)	I/O/T	GPIO45 <sup>3</sup>

[1] :

P: Power supply; I: Input; O: Output; T: High impedance.

[2] ([1](#),[2](#)):

GPIO0 and GPIO1 can be enabled by disabling the XTAL\_32K function, which can be achieved by moving R61 and R59 to R199 and R197, respectively.

[3] :

GPIO45 can be enabled by disabling the SD\_PWRn function, which can be achieved by moving R231 to R100.

## Hardware Revision Details

No previous versions available.

## Related Documents

- [ESP32-P4-Function-EV-Board Schematic](#) (PDF)
- [ESP32-P4-Function-EV-Board PCB Layout](#) (PDF)
- [ESP32-P4-Function-EV-Board Dimensions](#) (PDF)
- [ESP32-P4-Function-EV-Board Dimensions source file](#) (DXF) - You can view it with [Autodesk Viewer](#) online
- [1.0K-GT-15PB Specification](#) (PDF)
- [Camera Datasheet](#) (PDF)
- [Display Datasheet](#) (PDF)
- [Datasheet of display driver chip EK73217BCGA](#) (PDF)
- [Datasheet of display driver chip EK79007AD](#) (PDF)
- [LCD Adapter Board Schematic](#) (PDF)
- [LCD Adapter Board PCB Layout](#) (PDF)
- [Camera Adapter Board Schematic](#) (PDF)
- [Camera Adapter Board PCB Layout](#) (PDF)

For further design documentation for the board, please contact us at [sales@espressif.com](mailto:sales@espressif.com).

[← Previous](#)

[Next →](#)